





HARGROUND™

High Compression Grounding Series CGET

Compression Grounding Series CGET

Catalog Number	Cable to Cable or Cable to Ground Rod ①		Installation Data	
	Run (A)	Tap (B)	Die Index	No. of Crimps
CGET26	#6 Sol. - #2 Str., 1/4" Rod	#6 Sol. - #2 Str.	U-C	1
CGET2/06	#1 Str. - 2/0 Str., 3/8" Rod	#6 Sol. - #2 Str.	U-0	1
CGET2/01	#1 Str. - 2/0 Str., 3/8" Rod	#1 Str. - 2/0 Str.		1
CGET2506	3/0 Str. - 250 MCM, 1/2" - 5/8" Rod	#6 Sol. - 2/0 Str.	U997	1
CGET2503/0	3/0 Str. - 250 MCM, 1/2" - 5/8" Rod	3/0 Str. - 250 MCM		1
CGET5006	300 MCM - 500 MCM, 3/4" Rod	#6 Sol. - 2/0 Str.	U1011	2
CGET5003/0	300 MCM - 500 MCM	3/0 Str. - 250 MCM		2
CGET500300	300 MCM - 500 MCM	300 MCM - 500 MCM		3



- HarGround products are listed to UL467 and rated for Direct Burial.
- Add suffix "-A" for factory applied antioxidant.
- Add prefix "T-" for tinned.
- A 12-ton tool is required for these connections.



① Ground Rods must be precrimped. See below for die chart.

Ground Rod Dia.	Precrimping Dies
1/2"	U2CABT
5/8"	U2CABT
3/4"	U2CABT

② Clean rust and protective coatings from reinforcing steel prior to installation to provide proper ground connection. Precrimping is not required.

301 Ziegler Drive, Grayslake, IL 60030
 847-548-8700 • 800-842-7437 • Fax: 847-548-8755
 Web-site: www.harger.com • E-mail: hargersales@harger.com